



TAN FLEXTRA

Designed for tank truck and in-plant service. Ideal for conveying non-oily, abrasive materials such as sand, limestone, plastic pellets, and other dry abrasive products.

Performance + Specs

Tube

- Natural Rubber (NR)

Cover

- Tan SBR Gum Rubber (Corrugated) with Yellow Spiral Stripe (Wrapped Impression)

Reinforcement

- Spiral-plied Synthetic Fabric with Wire Helix

Temperature Range

- 40°F / -40°C ~ 180°F / 82°C

Design Factor

- 4:1

Packaging

- 1½"-4" – 100ft lengths, coiled and poly-wrapped
- 5"-6" – 50ft lengths, coiled and poly-wrapped

Coupling

- Refer to the Continental Industrial Hose Assembly Manual for crimp specifications.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

Continental Tan Flextra® with Pureten™ 75 PSI WP MADE IN CANADA

Tan Flextra

Order Codes: 549-116

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.59	40.48	400	Brown	300	2.07	2.50	63.50	29.00	736.60	75	0.52	0.68	1.01	20736621
1-1/4	31.75	1.84	46.83	400	Brown			3.00	76.20	29.00	736.60	75	0.52	0.81	1.20	20768513
1-1/2	38.10	2.11	53.63	100	Brown	300	2.07	3.00	76.20	29.00	736.60	75	0.52	0.99	1.47	20019210
2	50.80	2.61	66.33	100	Brown	300	2.07	4.00	101.60	29.00	736.60	75	0.52	1.25	1.86	20019212
2-1/2	63.50	3.15	80.03	100	Brown	300	2.07	5.00	127.00	29.00	736.60	75	0.52	1.74	2.59	20019213
3	76.20	3.69	93.69	100	Brown	300	2.07	6.00	152.40	29.00	736.60	75	0.52	2.17	3.23	20019216
4	101.60	4.69	119.25	100	Brown	300	2.07	9.00	228.60	29.00	736.60	75	0.52	2.96	4.40	20019217
4-1/2	114.30	5.25	133.46	100	Brown	300	2.07	11.00	279.40	29.00	736.60	75	0.52	3.82	5.68	20019220
5	127.00	5.80	147.36	50	Brown	300	2.07	12.50	317.50	29.00	736.60	75	0.52	4.46	6.64	20019221
				100	Brown	300	2.07	12.50	317.50	29.00	736.60	75	0.52	4.46	6.64	20132671
6	152.40	6.85	173.88	100	Brown	300	2.07	15.00	381.00	29.00	736.60	75	0.52	5.67	8.44	20019224