



TANKER BARGE DISCHARGE

Engineered for demanding marine petroleum transfer (dock-to-barge and barge-to-shore) operations, this premium black nitrile tanker barge hose delivers exceptional durability and performance in every critical discharge application. Designed to handle up to 50% aromatic content, it features a rugged built-in coupling with 150# RFSO ANSI-B16.5 / ASTM A105 flanges for reliable, corrosion-resistant connection integrity. Every assembly is thoroughly tested to ARPM IP-8 standards and meets U.S. Coast Guard Federal Regulations Title 33, Chapter 1, Subpart C, Clause 154.500—ensuring trusted safety, compliance, and long service life. A robust, high-quality solution for operators who demand reliability in the transfer of petroleum-based products.

Performance + Specs

Tube Nitrile (NBR)	Cover Chloroprene (CR)
Reinforcement Spiral-plyed Synthetic Fabric with Grounding Wires	Temperature Range -25°F / -32°C ~ 220°F / 104°C
Design Factor 4:1	Packaging Chloroplast heavy-duty packaging
Coupling Coupled with standard built-in steel nipple/150#RFSO flanges. Available in other bolt hole patterns, materials and floating flanges on request. Swage nipples are offered up to 10". Hose asse	Non Stock / Sizes Custom lengths available, contact customer service.

Branding

Continental Tanker Barge Discharge 200 PSI WP Nitrile

Tanker Barge Discharge
Order Codes: 541-426

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
2	50.80	2.71	68.88	100	Black	200	1.38	1.57	2.33	20137912
3	76.20	3.71	94.28	66	Black	200	1.38	3.12	4.64	20788415
4	101.60	4.84	122.88	30	Black	200	1.38	5.96	8.87	20266777
6	152.40	7.07	179.52	30	Black	200	1.38	10.87	16.17	20220877
				35	Black	200	1.38	10.24	15.24	21224560
				50	Black	200	1.38	9.12	13.58	21224011
				82	Black	200	1.38	8.10	12.05	20346083
8	203.40	9.08	230.52	25	Black	200	1.38	15.33	22.81	21193583
				30	Black	200	1.38	14.19	21.12	21001448
				100	Black	200	1.38	10.20	15.18	20736326
10	254.00	11.23	285.36	20	Black	200	1.38	25.39	37.78	20015535
				100	Black	200	1.38	14.81	22.04	21023336
				100	Black	200	1.38	12.17	18.11	21224548
12	305.44	13.43	341.04	16.5	Black	200	1.38	594.33	884.46	20259811