

TIG WELDING

A lightweight hose designed with maximum flexibility for use as a cable cover in the TIG welding hose process. The spiral reinforced, non-conductive EPDM compound is designed to handle air, cooling water, and inert shielding gases. The outer cover is resistant to abrasion, ozone and mild chemicals.

Performance + Specs

Tube

- EPDM Rubber
- Non-Conductive

Cover

- EPDM Rubber
- Non-Conductive

Reinforcement

- Spiral Synthetic Yarn

Temperature Range

- -40°F / -40°C ~ 200°F / 93°C

Design Factor

- 4:1

Packaging

- 500ft Reels
- Maximum 3 pieces, 25ft Minimum length

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Branding

Generic Brand

Tig Welding

Order Codes: 569-650

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1/4	6.00	0.44	11.20	500	Black	125	0.86	0.07	0.11	20666343
5/16	8.00	0.51	13.00	500	Black	125	0.86	0.08	0.13	20188094
					Black	125	0.86	0.08	0.13	20661435
3/8	9.50	0.59	15.00	500	Black	125	0.86	0.11	0.16	20751822
13/32	10.10	0.66	16.80	500	Black	125	0.86	0.15	0.22	20188095
					Black	125	0.86	0.15	0.22	20662082