



TORRIDAIR

When the heat is on, Continental delivers. Designed to handle non-oily hot air up to 400°F, this rugged hose is built for manifold blowers and in-plant compressors feeding dry bulk transfer systems. This hose is engineered to perform in the hottest environments. With superior heat resistance, flexibility, and durability, it's the go-to HOT Air solution. PWhile Pyroflex® Hot Air II offers reliable performance for many hot air transfer applications, our premium hot air hose is engineered to go further—handling higher temperatures, more demanding conditions, and longer service life.

Performance + Specs

Tube Super Thermo-Flo EPDM	Cover Super Thermo-Flo EPDM Synthetic Rubber (wrapped impression)
Reinforcement Spiral-plied Synthetic Fabric with Double Wire	Temperature Range -40°F / -40°C ~ 400°F / 204°C
Design Factor 4:1	Packaging 100ft lengths, Coiled & Poly-Wrapped
Coupling Refer to the Continental Industrial Hose Assembly Manual for crimp specifications.	Non Stock / Sizes For special production run minimum requirements, Contact Customer Service.

Branding

CONTINENTAL TORRIDAIR BLOWER HOSE 400 °F MAX 100 PSI WP MADE IN CANADA

Torridair

Order Codes: 549-856

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/4	31.75	1.74	44.09	100	Black	400	2.76	3.00	76.20	29.00	736.60	100	0.69	0.66	0.99	20258052
2	50.80	2.51	63.66	100	Black	400	2.76	5.00	127.00	29.00	736.60	100	0.69	1.07	1.59	20020255
2-1/2	63.50	3.01	76.36	100	Black	400	2.76	6.00	152.40	29.00	736.60	100	0.69	1.34	1.99	20020257
3	76.20	3.56	90.40	100	Black	400	2.76	9.00	228.60	29.00	736.60	100	0.69	1.82	2.71	20020260
4	101.60	4.58	116.25	100	Black	400	2.76	16.00	406.40	29.00	736.60	100	0.69	2.47	3.67	20020261
6	152.40	6.74	171.16	100	Black	400	2.76	30.00	762.00	29.00	736.60	100	0.69	5.07	7.54	20130428