



TWIN-LINE (GRADE R)

For welding service, Compatible with Oxygen & Acetylene Gases. Meets ARPM IP-7 standard for Grade R welding hose.

Performance + Specs

Tube EPDM Rubber	Cover EPDM Rubber
Reinforcement Spiral Synthetic Yarn	Temperature Range -40°F / -40°C ~ 120°F / 49°C
Design Factor 4:1	Packaging - 500ft Reels
Coupling Coupled assemblies available.	Non Stock / Sizes For special production run minimum requirements, Contact Customer Service.

Branding

Continental Twin-Line 1/4" Grade R Acetylene Only Std. Duty Max WP 200 PSI Meets ARPM IP-7 Made in USA

Twin-Line (Grade R)

Order Codes: 569-588

Product Numbers										
ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/16	4.80	0.44	11.10	500	Red / Green	200	1.38	0.15	0.23	20027120
				700	Red / Green	200	1.38	0.15	0.23	20762336
1/4	6.60	0.52	13.10	25	Red / Green	200	1.38	5.02	7.48	20027151
				50	Red / Green	200	1.38	10.08	15.00	20027152
				100	Red / Green	200	1.38	20.20	30.06	20027153
				500	Red / Green	200	1.38	0.20	0.30	20027170
				750	Red / Green	200	1.38	0.20	0.30	20525972
5/16	8.10	0.59	15.00	500	Red / Green	200	1.38	0.25	0.37	20027203
3/8	9.70	0.65	16.60	500	Red / Green	200	1.38	0.29	0.43	20027224