

GRADE T FUEL GAS STD DUTY MAX WP 200 PSI MEETS ARPM/IP-7/CGA E-1  

TWIN-LINE (GRADE T)

For welding service, compatible with all common welding fuel gases. Meets ARPM IP-7 and CGA E-1 standards for Grade T welding hose. Non-conductive.

Performance + Specs

Tube

- Chloroprene (CR)

Cover

- Nitrile / PVC Blend
- ARPM Class A (High Oil Resistance)

Reinforcement

- Spiral Synthetic Yarn

Temperature Range

- 40°F / -40°C ~ 120°F / 49°C

Design Factor

- 4:1

Packaging

- 500ft Reels

Coupling

- Coupled assemblies available.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

Continental Twin-Line 1/4" Grade T Fuel Gas Std. Duty Max WP 200 PSI Meets ARPM IP-7/Cga E-1. Made In USA

Twin-Line (Grade T)

Order Codes: 569-618

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/16	5.00	0.43	11.00	500	Red / Green	200	1.38	0.15	0.22	20027443
				700	Red / Green	200	1.38	0.15	0.22	20762458
1/4	6.40	0.53	13.40	50	Red / Green	200	1.38	10.30	15.33	20027453
				100	Red / Green	200	1.38	20.60	30.66	20027454
				500	Red / Green	200	1.38	0.21	0.31	20027465
5/16	8.10	0.59	15.00	500	Red / Green	200	1.38	0.24	0.36	20027480
3/8	9.70	0.66	16.70	25	Red / Green	200	1.38	6.95	10.34	20027493
				50	Red / Green	200	1.38	13.90	20.69	20027495
				100	Red / Green	200	1.38	27.76	41.32	20027497
				600	Red / Green	200	1.38	0.28	0.41	20027498