



VAPOR RECOVERY DOCK

For use in the recovery of petroleum vapors during the transfer of petroleum-based products between docks and tankers or barges.

Performance + Specs

Tube Nitrile (NBR)	Cover Nitrile / PVC Blend
Reinforcement Synthetic Fabric Plies Plus Two (2) Wire Helix	Temperature Range -25°F / -32°C ~ 200°F / 93°C
Design Factor 4:1	Packaging Chloroplast heavy-duty packaging
Coupling Built-in nipples (or swaged fittings up to 10" ID) fitted with 150# flange with extra 5/8" diameter hole located midway between flange bolt hole as per Coast Guard requirements.	Non Stock / Sizes Custom lengths available, contact customer service.

Branding

Continental Vapor Recovery 25 PSI Max WP

VAPOR RECOVERY DOCK

Order Codes: 541-090

Product Numbers														
ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
6	152.40	6.98	177.22	30	Black	22.00	558.80	29.00	736.60	25	0.17	10.91	16.24	20781274
8	203.40	8.96	227.49	40	Black	30.00	762.00	29.00	736.60	25	0.17	11.13	16.56	21164872
					Black	30.00	762.00	29.00	736.60	25	0.17	12.97	19.30	20116611
10	254.00	11.04	280.50	42	Black	40.00	1,016.00	29.00	736.60	25	0.17	16.81	25.02	21170783
					Black	40.00	1,016.00	29.00	736.60	25	0.17	19.35	28.79	20321395
12	305.44	13.07	331.93	67	Black	60.00	1,524.00	29.00	736.60	25	0.17	20.52	30.54	21151058
					Black	60.00	1,524.00	29.00	736.60	25	0.17	22.90	34.08	21203452
					Black	60.00	1,524.00	29.00	736.60	25	0.17	20.39	30.35	20870820
15	383.29	16.42	417.02	50	Black	80.00	2,032.00	29.00	736.60	25	0.17	63.34	94.27	21192467
					Black	80.00	2,032.00	29.00	736.60	25	0.17	38.36	57.09	20562076