



VELOCITY™ BEVERAGE TRANSFER

Velocity Beverage Transfer is primarily for liquid transfer. For beverage transfer of USDA, FDA and NSF-approved materials. Ideal for applications needing lightweight, flexible PVC hose such as milk processing, wineries and microbreweries, including: filtration, barreling, transfer, pressing, and storage and fermentation tanks. Clear PVC allows for visual confirmation of product flow.

Performance + Specs

Tube

- PVC Compound
- Meet FDA, 3-A
- NSF 61 Certified Tube Material

Cover

- PVC Compound

Reinforcement

- Polyester Synthetic Yarn
- High Density Rigid PVC

Temperature Range

- -13°F / -25°C ~ 158°F / 70°C

Design Factor

- 3:1

Packaging

- Coiled & Poly-Wrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Branding

CONTINENTAL (LOGO) VELOCITY (LOGO) BEVERAGE TRANSFER 100 PSI WP MADE IN USA

Velocity™ Beverage Transfer

Order Codes: 591-103

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/2	38.10	2.05	52.10	100	White / Clear	330	2.28	2.50	63.50	29.00	736.60	110	0.76	0.54	0.81	20806470
2	50.80	2.53	64.20	100	White / Clear	300	2.07	4.00	101.60	29.00	736.60	100	0.69	0.58	0.86	20806471
3	76.20	3.71	94.20	100	White / Clear	300	2.07	6.00	152.40	29.00	736.60	100	0.69	1.23	1.83	20806472
4	101.60	4.72	120.00	100	White / Clear	225	1.55	7.00	177.80	29.00	736.60	75	0.52	1.57	2.33	20810398