



VELOCITY WATER S/D

Continental Velocity™ Water Transfer Hose gets water where you need it, efficiently and fast. This tough clear PVC hose lets you see water in motion, even in the most demanding applications. The premium heavy-duty construction provides great durability. Whether you need full-suction or transfer, the Velocity™ WT is the hose for your jobsite.

Performance + Specs

Tube

- PVC Compound

Cover

- PVC Compound

Reinforcement

- Polyester Synthetic Yarn
- Rigid High-Density PVC Helix

Temperature Range

- 0°F / -18°C ~ 158°F / 70°C

Design Factor

- 3:1

Coupling

- Refer to the Continental Industrial Hose Assembly Manual for crimp specifications.

Branding

CONTINENTAL(LOGO) VELOCITY(LOGO) WATER SUCTION 110 PSI WP MADE IN USA DATE CODE

Velocity Water S/D

Order Codes: 591-101

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/2	38.10	2.05	52.10	100	Clear	330	2.28	2.50	63.50	29.00	736.60	110	0.76	0.54	0.80	20762594
2	50.80	2.53	64.20	100	Clear	300	2.07	4.00	101.60	29.00	736.60	100	0.69	0.58	0.86	20762595
3	76.20	3.73	94.70	100	Clear	300	2.07	6.00	152.40	29.00	736.60	100	0.69	1.25	1.86	20635650
4	101.60	4.71	119.70	100	Clear	225	1.55	7.00	177.80	29.00	736.60	75	0.52	1.56	2.32	20635651
6	152.40	7.19	182.70	100	Clear	210	1.45	10.00	254.00	29.00	736.60	70	0.48	4.19	6.23	20630166
8	203.20	9.29	236.00	20	Clear			15.00	381.00	29.00	736.60	60	0.41	5.66	8.42	20761732