



VERSAFUEL FLEX

VersaFuel™ Flex is a flexible and lightweight hose designed to convey a multitude of new fuels. Used by tank trucks and bulk petroleum stations to transfer diesel, gasoline, biodiesel blends up to B100, ethanol blends up to E100 and petroleum-based products with up to 60% aromatic content. Full suction rating.

Performance + Specs

Tube - Specially Compounded Nitrile (NBR) (Static Dissipating) - ARPM Class A (High Oil Resistance)	Cover - Nitrile / PVC Blend Flexwing Versafuel Cover - Material = Synthetic Rubber - Both Versafuel products should have same tube and cover material description - Corrugated - ARPM Class A (High Oil Resistance)
Reinforcement Spiral-Plied Synthetic Fabric With Double Wire Helix	Temperature Range -30°F / -34°C ~ 180°F / 82°C
Design Factor 4:1	Packaging Coiled and poly-wrapped.
Coupling - Refer to the ContiTech Industrial Hose Assembly Manual for crimp specifications Alternative Fuel Compatibility (Tubes & Covers)	Downloads

Branding

Continental VersaFuel™ Flex

Versafuel Flex

Order Codes: 543-636

Product Numbers															
ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number	
1	25.40	1.43	36.39	400	Black	1.00	25.40	29.00	736.60	250	1.72	0.49	0.73	20459628	
1-1/2	38.10	1.94	49.39	100	Black	1.50	38.10	29.00	736.60	250	1.72	0.74	1.10	20459629	
2	50.80	2.45	62.30	100	Black	2.00	50.80	29.00	736.60	250	1.72	0.96	1.43	20459650	
2-1/2	63.50	3.00	76.29	400	Black	2.50	63.50	29.00	736.60	200	1.38	1.35	2.01	20459651	
3	76.20	3.52	89.31	100	Black	3.00	76.20	29.00	736.60	200	1.38	1.65	2.46	20459652	
4	101.60	4.58	116.38	400	Black	4.00	101.60	29.00	736.60	150	1.03	2.48	3.69	20459655	