



VERSIFLO S&D

Designed for operations that demand more from a medium-duty hose, the Continental Versiflo® S&D delivers strong, reliable suction and discharge performance with elevated pressure capability. Its durable yet flexible construction makes it ideal for industrial, agricultural, and construction applications where consistent flow and higher working pressure are essential. Versiflo® 150 PSI (542-528/541-528) or 300 PSI (542-026), provides the strength you need without the weight of a heavy-duty hose.

Performance + Specs

Tube • EPDM Rubber	Cover • EPDM Rubber • Wrapped Finish
Reinforcement • Spiral-ply Synthetic Fabric • Double wire helix	Temperature Range • -25°F / -32°C ~ 200°F / 93°C
Design Factor • 3:1	Packaging 542-528 – Coiled & Poly-Wrapped 541-528 – Custom lengths
Coupling • Refer to the Continental Industrial Hose Assembly Manual for crimp specifications.	Non Stock / Sizes • For special production run minimum requirements, Contact Customer Service.

Branding

Continental Versiflo® 150 Water Suction & Discharge MADE IN CANADA

Versiflo S&D 150

Order Codes: 542-528 (1-1/4" to 6" 150 PSI), 541-528 (8" to 14" 150 PSI)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.05	1.10	27.90	100	Black	450	3.10	2.00	50.80	29.00	736.60	150	1.03	0.32	0.48	20752179
1	25.40	1.35	34.25	50	Black	450	3.10	2.00	50.80	29.00	736.60	150	1.03	0.41	0.61	20752248
				100	Black	450	3.10	2.00	50.80	29.00	736.60	150	1.03	0.41	0.61	20016819
				400	Black	450	3.10	2.00	50.80	29.00	736.60	150	1.03	0.41	0.61	20335103
				50	Black	450	3.10	4.00	101.60	29.00	736.60	150	1.03	0.50	0.75	20752260
1-1/4	31.75	1.60	40.59	100	Black	450	3.10	4.00	101.60	29.00	736.60	150	1.03	0.50	0.75	20016820
				400	Black	450	3.10	4.00	101.60	29.00	736.60	150	1.03	0.50	0.75	20304947
				100	Black	450	3.10	4.00	101.60	29.00	736.60	150	1.03	0.62	0.93	20016822
1-1/2	38.10	1.85	47.05	200	Black	450	3.10	4.00	101.60	29.00	736.60	150	1.03	0.62	0.93	20289478
				400	Black	450	3.10	4.00	101.60	29.00	736.60	150	1.03	0.62	0.93	20133451
				50	Black	450	3.10	7.00	177.80	29.00	736.60	150	1.03	0.81	1.21	20752271
2	50.80	2.35	59.74	100	Black	450	3.10	7.00	177.80	29.00	736.60	150	1.03	0.81	1.21	20016828
				200	Black	450	3.10	7.00	177.80	29.00	736.60	150	1.03	0.81	1.21	20127031
				300	Black	450	3.10	7.00	177.80	29.00	736.60	150	1.03	0.81	1.21	20016829
				400	Black	450	3.10	7.00	177.80	29.00	736.60	150	1.03	0.81	1.21	20066572
2-3/8	60.77	2.79	70.74	100	Black	450	3.10	9.00	228.60	29.00	736.60	150	1.03	1.04	1.55	20276866
2-1/2	63.50	2.89	73.47	100	Black	450	3.10	10.00	254.00	29.00	736.60	150	1.03	1.13	1.68	20016831
				400	Black	450	3.10	10.00	254.00	29.00	736.60	150	1.03	1.13	1.68	20140395
3	76.20	3.44	87.26	50	Black	450	3.10	14.00	355.60	29.00	736.60	150	1.03	1.51	2.24	20368397
3	76.20	3.43	87.04	100	Black	450	3.10	14.00	355.60	29.00	736.60	150	1.03	1.48	2.20	20016834
				400	Black	450	3.10	14.00	355.60	29.00	736.60	150	1.03	1.48	2.20	20016835
3-1/2	89.92	4.03	102.39	100	Black	450	3.10	16.00	406.40	29.00	736.60	150	1.03	1.96	2.91	20752316
4	101.60	4.45	112.95	100	Black	450	3.10	18.00	457.20	29.00	736.60	150	1.03	2.08	3.09	20016838
4-1/2	114.30	5.02	127.60	100	Black	450	3.10	20.00	508.00	29.00	736.60	150	1.03	2.70	4.02	20752318
5	127.00	5.54	140.63	50	Black	450	3.10	22.00	558.80	29.00	736.60	150	1.03	3.42	5.10	20140307
				400	Black			22.00	558.80	29.00	736.60	150	1.03	3.43	5.10	20706663
6	152.40	6.61	167.96	100	Black	450	3.10	24.00	609.60	29.00	736.60	150	1.03	4.78	7.11	20016843
8	203.40	8.78	222.98	20	Black	450	3.10	48.00	1,219.20	29.00	736.60	150	1.03	8.00	11.91	20115258
				100	Black	450	3.10	48.00	1,219.20	29.00	736.60	150	1.03	8.00	11.91	20070795
10	254.00	10.99	279.18	50	Black	450	3.10	60.00	1,524.00	29.00	736.60	150	1.03	12.84	19.11	20736382



Versiflo S&D 300

Order Codes: 542-026 (300 PSI)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.45	36.84	400	Black	6.00	152.40	29.00	736.60	300	2.07	0.54	0.80	20815070
1-1/4	31.75	1.70	43.19	100	Black	7.50	190.50	29.00	736.60	300	2.07	0.65	0.96	20692838
1-1/2	38.10	1.97	49.97	100	Black	9.00	228.60	29.00	736.60	300	2.07	0.82	1.22	20692839
				400	Black	9.00	228.60	29.00	736.60	300	2.07	0.82	1.22	21037304
2	50.80	2.48	63.05	400	Black	12.00	304.80	29.00	736.60	300	2.07	1.12	1.67	21011356
4	101.60	4.67	118.63	400	Black	24.00	609.60	29.00	736.60	300	2.07	3.01	4.48	21100089