



VINTNER LITE

Vintner™ Lite builds on the trusted performance of Vintner™ Reserve, offering a lighter-weight, more flexible solution for sanitary transfer of wine, beer, juice, dairy, and other liquid food products. Rated at 150 PSI, it is ideal for in-plant processing and transfer applications where ease of handling is critical without sacrificing hygiene or reliability. Reinforced with a crush-resistant, rust-proof monofilament helix, Available in three tube options to suit a wide range of applications: Chlorobutyl (549-915): Ideal for carbonated beverages, beer, juice, and acidic products, offering low permeability and chemical resistance (low-fat applications); EPDM (549-118 & 549-219): Excellent for heat resistance and demanding CIP processes, suited for non-oily applications; Nitrile (549-277): Best for oily and fatty food products, providing enhanced oil resistance. Vintner™ Lite delivers reliable performance, and sanitary compliance across a broad range of beverage and liquid food applications.

Performance + Specs

Tube - Meets FDA, USDA & 3-A Sanitary Standard 18-03 Certificate #3737 Standard 18-03) - EPDM 549-118 (Red), 549-219 (Gray) - Nitrile(NBR) 549-277 - Chlorobutyle 549-915	Cover - EPDM (Wrapped Finish) 549-118 & 549219 (EPDM), 549219, and 549-915 (CB) - Chemevic (NBR/PVC) 549-277
Reinforcement Spiral-plyed fabrics with monofilament helix	Temperature Range -30°F / -34°C ~ 220°F / 104°C
Design Factor 4:1	Packaging Coiled & Polywrapped
Coupling Refer to Continental Hose Assembly Manual, C-IQ or your fitting manufacturer for crimp specification.	

Branding

CONTINENTAL VINTNER LITE 150 PSI CB MEETS 3A 18-03 FDA USDA FDA USDA REQUIREMENT MADE IN CANADA

Vintner Lite Chlorobutyl (CIIR)

Order Codes: 549-915 (Chlorobutyle)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.48	37.59	100	Gray	600	4.14	4.00	101.60	27.00	685.80	150	1.03	0.50	0.74	21220863
1-1/2	38.10	1.98	50.29	100	Gray	600	4.14	6.00	152.40	27.00	685.80	150	1.03	0.70	1.04	21220864
2	50.80	2.48	62.99	100	Gray	600	4.14	9.00	228.60	27.00	685.80	150	1.03	0.90	1.34	21220865
2-1/2	63.50	3.11	78.99	100	Gray	600	4.14	12.00	304.80	27.00	685.80	150	1.03	1.45	2.16	21220866
3	76.20	3.69	93.73	100	Gray	600	4.14	15.00	381.00	27.00	685.80	150	1.03	1.97	2.93	21220867

Vintner Lite EPDM

Order Codes: 549-118 (Red EPDM), 549-219 (Gray EPDM)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.46	37.04	100	Gray	600	4.14	4.00	101.60	27.00	685.80	150	1.03	0.47	0.71	21129807
				400	Red	600	4.14	4.00	101.60	27.00	685.80	150	1.03	0.47	0.70	21088280
1-1/2	38.10	1.96	49.78	100	Gray	600	4.14	6.00	152.40	27.00	685.80	150	1.03	0.66	0.99	21129808
				200	Gray	600	4.14	6.00	152.40	27.00	685.80	150	1.03	0.66	0.99	21144620
				400	Red	600	4.14	6.00	152.40	27.00	685.80	150	1.03	0.66	0.98	21088281
2	50.80	2.50	63.50	100	Gray	600	4.14	9.00	228.60	27.00	685.80	150	1.03	0.94	1.40	21129810
				400	Gray	600	4.14	9.00	228.60	27.00	685.80	150	1.03	0.94	1.40	21156466
				400	Red	600	4.14	9.00	228.60	27.00	685.80	150	1.03	0.94	1.39	21088282
2-1/2	63.50	3.08	78.34	100	Gray	600	4.14	12.00	304.80	27.00	685.80	150	1.03	1.39	2.07	21129811
3	76.20	3.67	93.15	100	Gray	600	4.14	15.00	381.00	27.00	685.80	150	1.03	1.89	2.81	21129812

Vintner Lite Nitrile (NBR)

Order Codes: 549-277 (NITRILE)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.46	37.10	100	Gray	600	4.14	3.00	76.20	27.00	685.80	150	1.03	0.53	0.79	21170914
1-1/2	38.10	2.01	50.98	100	Gray	600	4.14	4.00	101.60	27.00	685.80	150	1.03	0.75	1.11	21170915
2	50.80	2.51	63.70	100	Gray	600	4.14	7.00	177.80	27.00	685.80	150	1.03	1.07	1.60	21170916
2-1/2	63.50	3.09	78.54	100	Gray	600	4.14	10.00	254.00	27.00	685.80	150	1.03	1.56	2.31	21170917
3	76.20	3.71	94.35	100	Gray	600	4.14	12.00	304.80	27.00	685.80	250	1.72	2.11	3.15	21170918