



WASHDOWN HD

Continental Washdown is a quality water discharge hose for the environments typically found in paper mills and other industrial operations. It can be supplied with an integral rubber tapered nozzle.

Performance + Specs

Tube

- SBR Rubber

Cover

- SBR Rubber
- Wrapped Finish

Reinforcement

- Spiral-Plied Synthetic Fabric

Temperature Range

- -25°F / -32°C ~ 200°F / 93°C

Design Factor

- 4:1

Packaging

- Coiled & Poly-Wrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure. Also available with integral tapered nozzle.

Non Stock / Sizes

- Hose: 400' minimum order in 400' increments
Hose with tapered nozzle: two 50' lengths in two-length increments

Branding

Continental Washdown HD, 150 PSI Max WP

Washdown HD

Order Codes: 542-298 (Green)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.05	1.19	30.25	50	Green			300	2.07	0.41	0.60	20032202
1	25.40	1.47	37.32	50	Green	29.00	736.60	300	2.07	0.54	0.80	20016504
1-1/4	31.75	1.72	43.67	50	Green	29.00	736.60	300	2.07	0.65	0.97	20016506
1-1/2	38.10	2.00	50.90	100	Green			300	2.07	0.82	1.22	20143481
2	50.80	2.55	64.88	50	Green			300	2.07	1.18	1.76	20029578