



WASHDOWN

Continental Washdown is a quality water discharge hose for the environments typically found in paper mills and other industrial operations. It can be supplied with an integral rubber tapered nozzle.

Performance + Specs

Tube SBR Rubber	Cover - SBR Rubber - Wrapped Finish
Reinforcement Spiral-plied Synthetic Fabric	Temperature Range -25°F / -32°C ~ 200°F / 93°C
Design Factor 4:1	Packaging Coiled & Poly-Wrapped
Coupling Contact fitting manufacturer for proper fitting recommendation and coupling procedure. Also available with integral tapered nozzle.	Non Stock / Sizes Hose: 400' minimum order/400' increments Hose with tapered nozzle: Two 50' lengths, two length increments

Branding

Continental 150 PSI Max WP

Washdown

Order Codes: 542-507 (White), 542-454 (Black), 542-455 (Green)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1/2	12.70	0.94	23.86	50	Green	450	3.10			150	1.03	0.30	0.45	20016732
				50	White	450	3.10			150	1.03	0.30	0.45	20016769
				50	White	450	3.10			150	1.03	0.30	0.45	20016768
				100	Green	450	3.10			150	1.03	0.30	0.45	20016734
				400	White	450	3.10			150	1.03	0.30	0.45	21154532
5/8	16.05	1.07	27.21	400	White	450	3.10			150	1.03	0.35	0.53	20593086
3/4	19.05	1.19	30.21	50	Black	450	3.10			150	1.03	0.39	0.58	20016718
				50	Green	450	3.10			150	1.03	0.40	0.60	20016736
				50	Green	450	3.10			150	1.03	0.40	0.60	20016735
				50	White	450	3.10			150	1.03	0.41	0.60	20016772
				50	White	450	3.10			150	1.03	0.40	0.60	20016773
				100	Black	450	3.10			150	1.03	0.39	0.58	20099823
				100	White	450	3.10			150	1.03	0.40	0.60	20016775
				100	White	450	3.10			150	1.03	0.41	0.60	20016774
				400	Black	450	3.10			150	1.03	0.39	0.58	20016721
				400	White	450	3.10			150	1.03	0.41	0.60	21154533
1	25.40	1.44	36.56	50	Black	450	3.10	29.00	736.60	150	1.03	0.49	0.73	20016722
				50	Green	450	3.10			150	1.03	0.51	0.75	20016741
				50	Green	450	3.10			150	1.03	0.51	0.75	20016740
				50	White	450	3.10			150	1.03	0.51	0.75	20016780
				50	White	450	3.10			150	1.03	0.51	0.76	20016779
				100	Black	450	3.10	29.00	736.60	150	1.03	0.49	0.73	20016723
				100	White	450	3.10			150	1.03	0.51	0.75	20016781
				400	White	450	3.10			150	1.03	0.51	0.76	21154534
1-1/4	31.75	1.69	42.91	50	Black	450	3.10			150	1.03	0.59	0.88	20016727
				50	Black	450	3.10			150	1.03	0.59	0.88	20016726
				50	Green	450	3.10			150	1.03	0.61	0.91	20016744
				50	Green	450	3.10			150	1.03	0.61	0.91	20016745
				50	White	450	3.10			150	1.03	0.61	0.91	20016783
				50	White	450	3.10			150	1.03	0.61	0.91	20016782
				100	Black	450	3.10			150	1.03	0.59	0.88	20016728
				100	White	450	3.10			150	1.03	0.61	0.91	20016784
				400	Black	450	3.10			150	1.03	0.59	0.88	20845915
1-1/2	38.10	1.99	50.46	50	Black	450	3.10	29.00	736.60	150	1.03	0.77	1.15	20016729
				50	Green	450	3.10			150	1.03	0.80	1.19	20016747
				50	White	450	3.10	29.00	736.60	150	1.03	0.80	1.19	20016785
				100	Black	450	3.10	29.00	736.60	150	1.03	0.77	1.15	20016730
				100	Green	450	3.10			150	1.03	0.80	1.19	20139579
2	50.80	2.49	63.16	50	Green					150	1.03	1.03	1.54	20016748