



WATER MOCCASIN

Water Moccasin transfer hose is recommended for the discharge of petroleum base products in marine applications. It is ideal for ship-to-shore fueling operations. Is designed with the proper balance of weight and rubber compounds to allow it to float in fresh or salt water when handling liquids with specific gravity of .90 or less. Handle petroleum product with up to 50% aromatic content. Oil, ozone, and weather resistant. (Formally Marathon)

Performance + Specs

Tube

- Nitrile (NBR)
- ARPM Class A (High Oil Resistance)

Cover

- Nitrile / PVC Blend - ARPM Class A (High Oil Resistance) (543-485) & (541-018)
- EPDM - ORANGE (543-894)

Reinforcement

- Synthetic Fabric, 2 Static Wires

Temperature Range

- -25°F / -32°C ~ 180°F / 82°C

Design Factor

- 4:1

Packaging

- Coiled, Wrapped and Palletized

Coupling

- Factory Assemblies available or contact fitting manufacturer for proper fitting recommendation and coupling procedure

Branding

CONTINENTAL WATER MOCCASIN FLOATING TRANSFER NITRILE 150 PSI MAX WP OIL SERVICE CAUTION:... MADE IN CANADA

Water Moccasin

Order Codes: 543-485 (1 1/2" - 4"), 541-485 (6" >), 543-894 (Orange EPDM)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.43	36.20	400	Black	600	4.14	150	1.03	0.49	0.73	20113716
1-1/2	38.10	2.05	52.10	100	Black	600	4.14	150	1.03	0.92	1.37	20068976
2	50.80	2.63	66.72	400	Black	600	4.14	150	1.03	1.34	2.00	20266175
2-1/2	63.50	3.13	79.42	200	Black	600	4.14	150	1.03	1.63	2.42	21148162
				400	Black	600	4.14	150	1.03	1.63	2.42	20315746
3	76.20	3.63	92.12	400	Black	600	4.14	150	1.03	1.92	2.85	20316460
3	76.20	3.58	90.92	400	Orange	600	4.14	150	1.03	1.72	2.56	21134454
4	101.60	4.66	118.40	400	Black	600	4.14	150	1.03	2.63	3.91	20017913
4	101.60	4.61	117.20	400	Orange	600	4.14	150	1.03	2.37	3.53	21050317
6	152.40	6.71	170.48	100	Black	600	4.14	150	1.03	4.18	6.22	20546582
				100	Black			150	1.03	4.18	6.22	20547026
				400	Black			150	1.03	4.18	6.22	20105881
8	203.40	8.80	223.56	100	Black	600	4.14	150	1.03	6.13	9.12	20589334