

WHITEWATER®

Whitewater® is for use on either steam cleaner machines or combination steam cleaner/pressure washer machines.

Performance + Specs

Tube

- Heat Resistant EPDM (Pyrosyn®)

Cover

- Chlorosulfonated Polyethylene Synthetic Rubber

Reinforcement

- One braid steel wire

Temperature Range

- 10°F / -23°C ~ 250°F / 121°C

Design Factor

- 4:1

Packaging

- 500ft reel, maximum 3 pieces, 50ft increments coupled lengths available

Coupling

- Refer to Continental Hose Assembly Manual or C-IQ for crimp specification.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service

Branding

Continental Whitewater® Pressure Washer 3000 PSI at 250°F (121°C) Steam Cleaner 350 PSI at 325°F (163°C) Made in USA

Whitewater®

Order Codes: 539-095 (Black)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/8	9.50	0.69	17.53	500	Black	12000	82.74	3000	20.68	0.25	0.37	20023806
				2500	Black	12000	82.74	3000	20.68	0.24	0.36	20303972
1/2	12.70	0.83	21.08	500	Black	10000	68.95	2500	17.24	0.33	0.49	20023820